

79.95 EUR

incl. 19% VAT, plus [shipping](#)

- Mini-STX !
- FANLESS !
- Premium Aluminium !



Slim 1U fanless Mini-STX case, boasting a compact volume of 1.07L. Sleek design and fanless operation make it perfect for noise-sensitive environments. Compatible with VESA mount monitors, it saves desk space for a clutter-free setup.

- Premium aluminium fanless CPU cooling design
- Small volume of 1.07L
- Optional 1U rackmount panels
- Wide application

|                              |                                                                                                                                                                                                                 |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Material</b>              | Aluminium with anodised black                                                                                                                                                                                   |
| <b>Motherboard Types</b>     | Mini-STX                                                                                                                                                                                                        |
| <b>Motherboard Support</b>   | (1) K3921-N mSTX / N1: Intel® Processor N50 (2C/6W) SoC<br>(2) K3921-N mSTX / N4: Intel® Processor N200 (4C/6W) SoC<br>(3) K3921-H mSTX / H1: Intel® Processor N100 (4C/6W) SoC                                 |
| <b>Maximum TDP Support</b>   | 10 W                                                                                                                                                                                                            |
| <b>Dimensions</b>            | 200.4 x 154.6 x 34.4 mm (W x D x H)                                                                                                                                                                             |
| <b>Front I/O Opening</b>     | USB-A 3.2 Gen1 x1, USB-C 3.2 Gen1 x1, Headphone x1, Microphone x1, Power button x1, COM port x1*<br>*Kontron K3921-N has two COM headers whereas K3921-H has one COM header                                     |
| <b>Rear I/O Opening</b>      | DC-In x1, Displayport x2, LAN x2**, USB 3.2 x4, COM port x1*<br>*Kontron K3921-N has two COM headers whereas K3921-H has one COM header<br>**Kontron K3921-N has two LAN ports whereas K3921-H has one LAN port |
| <b>Antenna Fitting Holes</b> | 2                                                                                                                                                                                                               |
| <b>Product Code</b>          | A-STX15-M1B                                                                                                                                                                                                     |
| <b>Optional</b>              | 1U Rackmount Panel<br>VESA Mounting                                                                                                                                                                             |